



Transmax Axle Long Life 75W-140

Heavy Duty Axle Fluid

Description

Castrol Transmax Axle Long Life 75W-140 is a full synthetic final drive lubricant which is suitable for use in axles and final drives in commercial vehicles and passenger cars where API GL-5 performance is required. Transmax Axle Long Life 75W-140 is included in the Scania High Performance product list and is approved against Scania STO 2:0A.

Advantages

- Excellent anti-wear and extreme pressure performance at all ambient temperatures and load conditions provide better final drive protection leading to longer life and reduced repair costs.
- Excellent cold flow properties reduces torque loss and increases efficiency.
- Improved protection at start up and in cold conditions.
- Excellent thermal and oxidative stability combined with superb temperature reduction Protects against pitting.
- Excellent shear stability permitting longer oil and component life.
- Extended drain reduces repair costs.

Typical Characteristics

Name	Method	Units	Transmax Axle Long Life 75W-140
Density @ 15C, Relative	ASTM D4052	g/ml	0.8698
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	25.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	182
Viscosity Index	ASTM D2270	None	170
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	147000
Pour Point	DIN-ISO 3016	°C	-54
Flash Point, COC	ASTM D92	°C	234

Product Performance Claims

API GL-5
Scania STO 2:0A

Transmax Axle Long Life 75W-140
07 Mar 2022
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com