



Castrol EDGE Professional Longlife III 0W-30

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE Professional is micro-filtered and certified CO₂ Neutral according to the highest global standard*. Its patented Fluid TITANIUM transforms to be stronger under pressure and reduces friction for maximum engine performance when you need it most.

Castrol EDGE Professional with Fluid TITANIUM: unlock the true performance of your engine.

** in accordance with the BSI PAS 2060 specification*

Application

Castrol EDGE Professional Longlife III 0W-30 is a full synthetic engine oil approved for use in automotive petrol and diesel vehicles where a VW 504 00 / 507 00 0W-30 lubricant is required.

Castrol EDGE Professional Longlife III 0W-30 is approved for use in Porsche vehicles where a Porsche C30 specification 0W-30 lubricant is required.

Please refer to your owners handbook.

Advantages

Castrol EDGE Professional Longlife III 0W-30 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's sophisticated vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE Professional Longlife III 0W-30:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across all engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature performance

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional Longlife III 0W-30
Density @ 15C, Relative	DIN 51757	g/ml	0.843
Viscosity, Kinematic 100C	DIN 51562	mm ² /s	12.3
Viscosity, Kinematic 40C	DIN 51562-1	mm ² /s	61
Viscosity Index	DIN ISO 2909	-	205
Pour Point	ASTM D97	°C	-48
Flash Point, PMCC	DIN EN ISO 2719	°C	196
Ash, Sulphated	DIN 51575	% wt	0.85
Viscosity, CCS -35C	DIN 51377	mPa.s (cP)	5930

Product Performance Claims

Porsche C30, VW 504 00/ 507 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional Longlife III 0W-30

07 Oct 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)
www.castrol.co.nz www.msds.castrol.co.nz