



Hysol CGX 100

High performance semi synthetic metalworking fluid

Description

Castrol Hysol™ CGX 100 is a high performance semi synthetic metalworking fluid formulated without boron and formaldehyde releasing agents. It contains an additive package that may help to enhance machining performance and surface finish. It also provides excellent product stability which helps to lower the overall operational costs.

Castrol Hysol CGX 100 is suitable for large central systems and single sump machines.

Application

Castrol Hysol CGX 100 is especially designed for machining of steel, stainless steel and aluminium alloys.

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	ü	ü ü ü	ü ü ü	ü ü		ü
Milling, Turning (general machining)	ü	ü ü ü	ü ü ü	ü ü		ü
Drilling	ü	ü ü ü	ü ü ü	ü ü		ü
Reaming, Tapping	ü	ü ü ü	ü ü ü	ü ü		ü
Broaching	ü	ü ü ü	ü ü ü	ü ü		ü

Advantages

- Formulated without formaldehyde releasing agent and boron which help you to fulfil aspects of legislative requirements and waste treatment requirements that specify that these chemicals are excluded
- Extended fluid life can help reduce maintenance and machine downtime
- Low foam in recommended water conditions (see details below)
- Lubrication package designed to try to help to enhance tool life and improve surface finish on aluminium machining
- Good wetting properties can help reduce coolant drag out and help deliver cleaner machine tools and components
- Suitable for a wide range of materials and applications provides opportunity for product consolidation

Typical Characteristics

Name	Method	Units	Value
Concentrate			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	20
Emulsion			
Appearance	Visual		Milky
pH (5%)	DIN 51369 ASTM E70-97		9.8
Refractometer Factor			1.0

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding	5-7%
General Machining	6-10%
Drilling	6-10%
Reaming and tapping	7-12%
Broaching	7-12%
Water range	50-800 ppm CaCO ₃

Storage

To avoid product deterioration always keep the container/drum tightly sealed. For optimum product stability, store between 5°C/41°F and 45°C/113°F in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. It is preferable to store the product indoors.

For more details, please refer the product safety data sheet.

Hysol CGX 100
28 Sep 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>