



Castrol Motorcycle Brake Fluid

High performance brake fluid

Description

Castrol Motorcycle Brake Fluid is a fully synthetic, high performance brake fluid, which maximises braking power in motorcycles and scooters.

Application

Castrol Motorcycle Brake Fluid is suitable for all motorcycles and scooters requiring DOT 3 or DOT 4 performance. Unsuitable for Harley Davidson, who only recommend a DOT 5 brake fluid with a silicone base.

Advantages

- Increased braking performance
- Resistance to high temperature vapour lock
- Increased braking safety margin when compared to conventional products
- Grand Prix Series

Typical Characteristics

Name	Method	Units	Typical
Appearance	Visual	-	Clear & bright yellow liquid
Density @ 20C	IP 160	g/ml	1.067
ERBP (Equilibrium Reflux Boiling Point)	ASTM D1120	°C	275
Wet Equilibrium Reflux Boiling Point	SAE J1703	°C	165
Viscosity, Kinematic -40C	IP 71	mm ² /s	1200
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	2.62
pH	SAE J1703	pH	7.2

Product Performance Claims

4925 Class 4
SAE J1704
FMVSS DOT 4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Motorcycle Brake Fluid
21 Oct 2016
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com