



## Castrol Power Steering Fluid

### PRODUCT DESCRIPTION

**Castrol Power Steering Fluid** is a mineral oil based fluid suitable for most power steering systems.

### PRODUCT APPLICATION

**Castrol Power Steering Fluid** is formulated to conform with power steering lubricant requirements of many car manufacturers where Dexron® II, III or Mercon performance is required. In addition to cars Castrol Power Steering Fluid is also suitable for light Commercial Vehicles (LCV's) and also trucks and buses where specified by the OEM.

**Castrol Power Steering Fluid** is suitable for power steering systems where the following fluids are specified:

Dexron® II: Dexron® III  
Ford M2C 138 CJ  
Ford Mercon  
Type A, Suffix A  
Ford M2C 166H  
Ford M2C-33 F or G  
SAE 10W engine oil: e.g., API SF, SG, SG, CC, CD  
SAE 10W-20 engine oil  
ISO 32 or 46 hydraulic oil  
Mitsubishi Power Steering Fluid

**N.B.** **Castrol Power Steering Fluid** is NOT recommended for power steering systems where special fluids are specified e.g., SAAB, Honda, Mercedes-Benz etc. **Castrol Power Steering Fluid** should NOT be used in engines even where SAE 10W or SAE 10W-20 is recommended.

### PRODUCT BENEFITS

- Compatible with other power steering fluids thus can be used for topping up existing systems.
- Assists in reducing power steering "squeal".
- Assists in reducing wear.
- Provides year-round power steering system protection.
- Assists in reducing corrosion and rust in power steering systems thus extending system component life.
- Helps in controlling power steering system leaks.
- Effective oxidation and foam control.
- Dyed RED to assist in locating leaks.
- Prove compatibility with a wide range of seal materials, thus reducing leaks.
- Increased resistance to oil oxidation and degradation.
- Improved protection of copper and bronze components.



DIRECTIONS FOR USE

- When adding power steering fluid, always follow the manufacturers recommendations (generally located in the Operators Manual).
- Fill power steering oil reservoir to MAXIMUM level only.
- DO NOT OVERFILL THE POWER STEERING OIL RESERVOIR.

TYPICAL CHARACTERISTICS

SAE Viscosity Grade	KV @ 100 °C (cSt)	KV @ 40°C (cSt)	Density @ 15°C	Viscosity Index	Pour Point (°C)	Closed Flash Point (°C)	Colour
10W	7.1	37	0.871	160	-40	185	Red

For further information of this or other Castrol products, visit our website [www.castrol.com.au](http://www.castrol.com.au)

Product Removal

- Bare Metal Surfaces:** Remove with Castrol solvent cleaners or water based degreasers.
- Hand Cleaning:** Use any of the Castrol range of hand cleaners, e.g. CareClean Plus.
- Other Surfaces:** Contact the Castrol Technical Advice Line on 1300 557 998.

Castrol Power steering Fluid

Castrol\_Power\_Steering\_Fluid\_3374393\_2013-11 replaces Castrol\_Power\_Steering\_Fluid\_3374393\_2011\_08 November 2013

Castrol Power steering Fluid and the Castrol logo are trademarks of Castrol Limited, used under license

Castrol Australia Pty Limited, - ABN 87 008 459 407 GPO Box 5222, Melbourne VIC 3001  
Technical Advice Line 1300 557 998 / Customer Service 1300 554 890  
[www.castrol.com.au](http://www.castrol.com.au)

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See <http://www.msds.castrol.com.au/>. No responsibility is taken by either Castrol Australia Pty Limited, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.