



## Power 1 Scooter 4T 10W-30

Scootek Technology

### Description

Castrol Power 1 Scooter 4T 10W-30 with Scootek Technology is an advanced, premium quality, low friction, 4-stroke engine oil designed specifically for modern scooter engines.

Unlike conventional 4T bikes with integral clutch and gearbox, the 4T Scooter uses a belt driven CVT (Continuously Variable Transmission) to transmit power from the crankshaft via a reduction gearbox to the rear wheel.

The scooter engine is often more compact, enclosed by bodywork, and spends a high proportion of time at full throttle.

As a result, scooter engines often run hotter than conventional 4T motorcycle engines.

Castrol Power 1 Scooter's fast flowing, low friction, Power Release formula is specially designed to reduce internal losses in the engine and resist the stresses of high temperature operation - enabling your Scooter to deliver maximum power without compromising protection.

### Application

Castrol Power 1 Scooter 4T is suitable for all modern 4-stroke scooter engines where JASO MB specifications are recommended.

Due to the incorporation of molybdenum based friction modifiers, this product is NOT suitable for wet clutch applications.

### Advantages

- Advanced 4-stroke scooter engine oil formulation with Scootek Technology
- Power Release formula for maximum and sustained engine performance
- Extreme high temperature air-cooled and water-cooled engine performance
- No compromise scooter engine protection
- Complies with requirements of catalyst equipped engines
- Good oil consumption & oxidation control

## Typical Characteristics

Name	Method	Units	POWER 1 Scooter 4T 10W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	10.5
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	5000
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	66
Viscosity Index	ASTM D2270	None	151
Pour Point	ASTM D97	°C	-
Flash Point, PMCC	ASTM D93	°C	-

## Product Performance Claims

API SL  
JASO MB

Power 1 Scooter 4T 10W-30  
04 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)