



## Radicool

Summer coolant and antifreeze.

### Description

Castrol Radicool is an engine coolant concentrate for year-round use in both petrol and diesel vehicles with aluminium or cast iron engines. This coolant can be diluted to 33 vol% concentration with purified water to give freeze protection down to -18°C, or at a 50 vol% dilution to provide freeze protection down to -36°C if required. To maintain optimum performance this product should be drained and replaced after 2 years.

### Application

Castrol Radicool is compatible with all materials normally used in automotive cooling systems including hoses, gaskets, seals, plastics and all metal components. It may be used in a variety of vehicles including passenger cars, SUVs and light commercial vehicles.

In the majority of cases, coolants are not compatible and should not be mixed with other coolants unless directed by the equipment manufacturer. If using Castrol Radicool for the first time, ensure that the cooling system has been adequately flushed with clean water before use.

When top up of the cooling system is necessary, add only Castrol Radicool concentrate mixed with demineralised water at the recommended concentration (or alternatively use Castrol Radicool Premix). For improved anti-boil and freeze protection, dilute Radicool concentrate at 50 vol%.

### Advantages

Castrol Radicool is a mixture of monoethylene glycol and selected chemical inhibitors. It contains no nitrites, phosphates or amines.

Castrol Radicool provides :

- Effective engine cooling without boiling
- Protection against corrosion of the alloys used in the cooling system of modern vehicles
- Compatibility with conventional seal and hose materials used in engine cooling systems
- Protection against cavitation corrosion
- Effective lubrication of water pumps
- Contains bittering agent

Castrol Radicool contains no phosphates, therefore potential problems of deposit formation with hard water in some modern engines are reduced.

## Typical Characteristics

Name	Method	Units	Castrol Radicool
Appearance	Visual	-	Clear & Bright
Colour	Visual	-	Green
pH, Engine Coolants (50% v/v)	ASTM D1287	pH	7.6
Boiling Point (undiluted)	ASTM D1120	°C	176
Freezing Point, 33% v/v	ASTM D1177	°C	-18
Freezing Point, 50% v/v	ASTM D1177	°C	-37
Density @ 20C	ASTM D4052	g/ml	1.13

## Product Performance Claims

ASTM D3306 (I)

Engine coolant concentrate ("antifreeze") conforms to the requirements of BS 6580:2010

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Radicool

25 Jun 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia  
Technical Advice Line 1300 557 998 Customer Service 1300 554 890  
[www.castrol.com.au](http://www.castrol.com.au) [www.msds.castrol.com.au](http://www.msds.castrol.com.au)