



Castrol POWER1 A747

Racing Lubricant

Description

Castrol POWER1 A747 is a low ash, part synthetic racing lubricant specially formulated for use in multi-cylinder, water-cooled two-stroke engines fitted to road racing machines, where combustion chamber deposit control is essential. It also contains special additives to prevent throttle slide sticking in wet weather conditions and may be used at fuel/oil ratios up to 40:1.

Application

Castrol POWER1 A747 is intended for racing applications only. It is not suitable for autolube systems and should not be mixed with any other oil, whether mineral, vegetable or synthetic.

Advantages

Castrol POWER1 A747 :

- Provides outstanding high speed / high temperature lubricity
- Ensures optimum control of piston and combustion chamber deposits
- Prevents throttle slide sticking in wet weather conditions

Typical Characteristics

Name	Method	Units	POWER1 A747
Density @ 15C, Relative	ASTM D4052	g/ml	0.93
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	19.7
Pour Point	ASTM D97	°C	-21
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	178
Viscosity Index	ASTM D2270	None	127

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 A747

23 Oct 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com