

## Magna™ SW D Range

Slideway oils

### Description

Castrol Magna™ SW D (previously called Magnaglide D Range) is specially formulated for the lubrication of slideways on machine tools. These oils are fortified with selected oiliness, extreme pressure additives and a special material to impart tackiness and adhesiveness.

Magna SW D lubricants are noted for their usual ability to overcome the stick-slip motion ordinarily associated with slow moving tool parts. They reduce machine tool carriage chatter and possess the necessary adhesive characteristics to prevent squeezing out of the lubricant.

### Application

- Magna SW D can be used on all horizontal and vertical slideways where a high quality demulsifying lubricant is required for slideway protection and to maximize coolant life; the outstanding frictional characteristics of the products prevents stick-slip, improving surface finish and tolerances of machined components and reducing rejection rates.
- Magna SW D meets the exacting demands in the following applications; planers, grinders, horizontal boring machines, shapers, jig borers, and milling machines.
- Magna SW D 32 can be used as a combined hydraulic and slideway oil.
- The Magna SW D range meets the requirements of:
  - Cincinnati Lamb (Milacron) P-47, P-50 and P-53 (depending on viscosity grade)
  - DIN 51502 – CGLP
  - DIN 51524 Part II (July 2004) – including ISO 13357-1/-2 filtration test
  - Suitable for Müller Weingarten equipment as hydraulic oil

### Advantages

- Outstanding demulsifying properties – helps prevent soluble oil emulsions on plastic slideway surfaces.
- Avoids downtime and expensive slideway repair or replacement.
- Exceptional resistance to stick slip – helps to ensure highly accurate and repeatable machining.
- High quality output is maintained.
- Protects metals against staining and corrosion.
- Oil-wetted surfaces remain in good condition.
- Avoids downtime and expensive slideway repair or replacement.
- Highly filterable – filters in oil supply remain unblocked

## Typical Characteristics

Name	Method	Units	SW D 32	SW D 68	SW D 100	SW D 150	SW D 220
ISO Viscosity Grade	-	-	32	68	100	150	220
Density @ 15°C / 59°F	ASTM D4052 / ISO 12185	kg/m <sup>3</sup>	870	880	890	890	890
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm <sup>2</sup> /s	32	68	100	150	220
Kinematic Viscosity @ 100°C / 212°F	ASTM D445 / ISO 3104	mm <sup>2</sup> /s	5.4	8.7	11.1	14.5	19.2
Viscosity Index	ASTM D2270 / ISO 2909	-	102	99	98	98	98
Pour Point	ASTM D97 / ISO 3016	°C/°F	-15/5	-12/10	-12/10	-12/10	-9/15
Flash Point - open cup method	ASTM D92 / ISO 2592	°C/°F	206 / 403	232 / 450	232 / 450	232 / 450	249 / 480
Rust test - distilled water (24 hrs)	ASTM D665A / ISO 7120	-	Pass				
Rust test - synthetic seawater (24 hrs)	ASTM D665B / ISO 7120	-	Pass				
Copper corrosion (3 hrs@100°C/ 212°F)	ASTM D130 / ISO 2160	Rating	1b				
Brugger test	DIN 51347	N/mm <sup>2</sup>	-	44	-	-	-
Four Ball Wear test - Wear Scar Diameter (40 kgf / 75°C / 1200 rpm / 1 hr)	ASTM D2266	mm	0.3	0.3	0.3	0.3	0.32
Four Ball Weld Load test - Weld Point	ASTM D2783	kgf	170	180	180	190	200
Stick-slip ratio - Cincinatti Lamb test	Cincinatti Lamb test	Ratio	0.74				
Cincinatti Lamb Specification	-	-	P-53	P-47	-	-	P-50

Subject to usual manufacturing tolerances.

**This product was previously called Magnaglide D Range. The name was changed in 2015.**

Magna™ SW D Range

19 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre, Whitchurch Hill, Pangbourne, Reading, RG8 7QR, United Kingdom

[www.castrol.com/industrial](http://www.castrol.com/industrial)