



Product Data

Castrol POWER1 4T 10W-30

OUTSTANDING PERFORMANCE AND ACCELERATION

Description

New Castrol POWER1 with 3-in-1 synthetic technology is engineered to deliver outstanding performance and acceleration.

Application

Castrol POWER1 4T 10W-30 is suitable for motorcycles which require API SP (or lower) and JASO MA2 engine oils.

Advantages

Castrol POWER1 4T 10W-30 with the power of 3-in-1 SYNTHETIC TECHNOLOGY delivers:

- Excellent acceleration
- Excellent protection
- Smooth riding

Synthetic Technology 4-stroke two-wheeler engine oil.

Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Castrol Power 1 4T 10W-30
Relative Density @ 15 °C	ASTM D4052	g/ml	0.863
Kinematic Viscosity @ 100 °C	ASTM D445	cST	11
Kinematic Viscosity @ 40 °C	ASTM D445	cSt	73
Viscosity Index	ASTM D2270	-	144
Pour Point	ASTM D93	°C	-37
Flash Point, Closed Cup	ASTM D97	°C	210

Performance

API SP
JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 4T 10W-30
12 Dec 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com