



## Pyroplex Gold

Aluminum Complex Grease

### Description

Castrol Pyroplex Gold® is a uniquely formulated, semi-synthetic, aluminum complex grease that excels in heavily loaded construction, mining, and industrial equipment where extreme operating conditions prevail. Castrol Pyroplex Gold contains a high level of synergistic solids, including 6% molybdenum disulfide, for maximum surface adhesion and added extreme pressure characteristics. It's tough, durable lubricating film will protect all lubricated parts in high shock loads and boundary conditions.

Pyroplex Gold's hydro-activated® polymers coupled with the aluminum complex thickener and carefully selected semi synthetic base fluids provide optimum "stay-in-place" ability and performance in the presence of very wet and or high humidity environments. The advanced formulation couples extreme pressure performance and "stay-in-place" ability in selected applications with outstanding mobility through all seasons.

Pyroplex Gold (NLGI 2) has assured pumpability in most cold environments that eliminates the traditional approach of changing to a NLGI 1 grade in winter. Castrol Pyroplex Gold has exceptional extreme pressure and high temperature performance as demonstrated through field test conditions and the Timken and Four-Ball Weld tests.

### Application

Castrol Pyroplex Gold will excel in multiple bearing applications, sliding applications, bucket pins, highly shock loaded areas, and asphalt paver auger bearings where extreme pressure and high heat exist.

### Advantages

Castrol Pyroplex Gold delivers:

- Extreme pressure and anti-wear performance especially in highly shock loaded areas.
- 6% molybdenum disulfide solids.
- Semi-synthetic basestock for unique cold flow and pumping capabilities.
- Excellent thermal stability with a high dropping point
- Enhanced "stay in place" technology with hydro-activated polymers providing very low water spray off rates

## Typical Characteristics

Name	Method	Units	Pyroplex Gold 2
Thickener Type	-	-	Aluminum Complex
Colour	Visual	-	Gold
Appearance	Visual	-	Tacky
Penetration @ 77 EF, Worked Grease , 60 Strokes	ASTM D217	-	275
Viscosity, Kinematic @ 40°C	ASTM D445	mm <sup>2</sup> /s	232
Viscosity, Kinematic @ 100°C	ASTM D445	mm <sup>2</sup> /s	23
Dropping Point	ASTM D2265	°F	500
Four Ball Wear Scar	ASTM D2266	mm	0.39
Four Ball EP Properties, Weld Point (Kg)	ASTM D2596	Kg Load	800
Timken OK Load	ASTM D2509	lb	70
Water Spray Off, Grease Loss	ASTM D4049	% wt	15
Corrosion Prevention	ASTM D1743	-	Pass
Copper Corrosion	ASTM D4048	-	1A
Wheel Bearing Life	ASTM D3527	hrs	140
Mobility @ 77°F	USS	g/min	624
Mobility @ 60°F	USS	g/min	305
Mobility @ 40°F	USS	g/min	85
Mobility @ 0°F	USS	g/min	12

Subject to usual manufacturing tolerances.

Pyroplex Gold

28 Nov 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)