



Castrol GTX Diesel 15W-40

Superior diesel engine protection

Description

Castrol GTX is one of the world's most trusted engine oils.

GTX Diesel is designed specially for today's automotive diesel engines. It's more than just oil.

It's liquid engineering that fights diesel engine problems that your engine faces every day, like soot and harsh deposits.

Why is this important? Because soot and harsh deposits can make the oil thicker; blocking oil ways, causing wear and decreasing performance.

Castrol GTX Diesel is engineered to clean away and protect against harmful diesel engine deposits.

Application

Castrol GTX Diesel 15W-40 is suitable for use in automotive diesel engines including inter-cooled and turbo-charged engines

where the manufacturer recommends an API CH-4 or earlier specification 15W-40 lubricant.

Castrol GTX Diesel 15W-40 is approved for use in diesel passenger car vehicles manufactured by TATA Motors that require a 15W-40 lubricant.

Advantages

Castrol GTX Diesel provides superior protection for your diesel engine:

- Outstanding diesel engine wear protection
- Superior cleaning power to maintain engine performance
- Reduces build up of harsh deposits
- Helps prevent oil from thickening and keeps it flowing freely

Typical Characteristics

Name	Method	Units	Castrol GTX Diesel 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.87
Viscosity, Kinematic 100C	IP 71	mm ² /s	14.7
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	109.0
Viscosity Index	ASTM D2270	None	139
Pour Point	ASTM D97	°C	-45
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.3
Ash, Sulphated	ASTM D874	% wt	1.35
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	5400
Flash Point, COC	ASTM D92	°C	246

Product Performance Claims

API CH-4

Tata approved

Castrol GTX Diesel 15W-40

10 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com