



Transmax Offroad 50

Powershift Transmission Fluid

Description

Castrol Transmax Offroad 50 is a transmission lubricant using highly refined mineral oil, designed for use in powershift transmissions, direct drive transmissions, wet disc brakes, final drives and differentials in off road machinery where Caterpillar TO-4 is required, and Recommended for use in Komatsu off-road machinery drivetrain and hydraulics.

Advantages

- Excellent oxidation stability maintains high temperature performance and transmission cleanliness during service life.
- Stable friction characteristics eliminate slippage and reduce brake noise.
- Excellent friction performance with a wide range of friction materials ensures smooth positive changes and enhanced friction material durability.
- Improved wear performance extends component life.

Typical Characteristics

Name	Method	Units	Transmax Offroad 50
Density @ 15C, Relative	ASTM D4052	g/ml	0.899
Appearance	Visual	-	Clear & bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	18.3
Pour Point	ASTM D97	°C	-15
Viscosity, Brookfield @ -15C	ASTM D2983	mPa.s (cP)	<150000
Viscosity Index	ASTM D2270	None	95
Flash Point, COC	ASTM D92	°C	>160

Caterpillar TO-4
suitable for use for Komatsu

Product Performance Claims

Cat TO-4

Recommended for use in Komatsu Equipment

Transmax Offroad 50

16 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

PT.Castrol Indonesia, Perkantoran Hijau Arkadia, Tower B, 9th floor. Jl. Let Jend, Simatupang Kav 88, Jakarta 12520, Indonesia

Customer Service: 0807 1 932273

www.castrol.com