



## Castrol POWER1 Scooter 4T 10W-40

Superior Acceleration at the Touch of the Throttle

### Description

Castrol POWER1 Scooter 4T is specifically designed for automatic scooter and bike owners who love the exhilaration of riding.

Castrol POWER1 Scooter 4T 10W-40 with **Scootek Technology™** is an advanced, premium quality, synthetic technology, low friction engine oil designed specifically for modern, 4-stroke, automatic transmission scooter and bike engines.

Scooter engines can run up to **15°C hotter** compared to motorcycles.

Castrol POWER1 Scooter 4T with **Scootek Technology™** is proven to reduce friction at high temperatures, helping deliver superior acceleration. **Scootek Technology™** enables this by delivering a low friction coefficient and providing superior thermal resistance for improved high temperature deposit control and resistance to oxidation.

### Application

Castrol POWER1 Scooter 4T 10W-40 is suitable for 4-stroke automatic bikes of all manufacturers where API SN (or below) and JASO MB specifications are recommended. Strictly not to be used in wet clutch motorcycle engines.

### Advantages

- Tested and proven to deliver superior acceleration at the touch of the throttle
- POWER1 Scooter with Scootek Technology™ is 0.5 metres ahead of leading competitor\*
- POWER1 Scooter 4T with **Scootek Technology™** reduces friction at high temperatures
- POWER1 Scooter 4T with **Scootek Technology™** reduces internal engine losses to friction
- POWER1 Scooter 4T with **Scootek Technology™** provides superior thermal resistance for improved high temperature deposit control and resistance to oxidation

\*In a 50 second full throttle acceleration test conducted by Castrol, with a Honda ANC125 scooter engine

## Typical Characteristics

Name	Method	Units	POWER1 Scooter 4T 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.8652
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	13.9
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	91.83
Viscosity Index	ASTM D2270	None	154
Pour Point	ASTM D97	°C	-37.5
Flash Point, PMCC	ASTM D93	°C	207.25

## Product Performance Claims

API SN  
JASO MB

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 Scooter 4T 10W-40

05 Jan 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)