



EDGE 0W-20 LL-17 FE+

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE with patented Fluid TITANIUM transforms its physical structure to be stronger under pressure to keep metal apart and reduces friction for maximum engine performance when you need it most.

Castrol EDGE with Fluid TITANIUM: unlock the true performance of your engine

Application

Castrol EDGE 0W-20 LL-17 FE+ is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an ACEA C5, API SP 0W-20 Lubricant.

Castrol EDGE 0W-20 LL-17 FE+ is Approved for use in vehicles that require a BMW Longlife-17FE+ 0W-20 lubricant.

Please refer to your owners handbook.

Advantages

Castrol EDGE 0W-20 LL-17 FE+ with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE 0W-20 LL-17 FE+:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature

Typical Characteristics

Name	Method	Units	Castrol EDGE 0W-20 LL-17 FE+
Density @ 15C, Relative	ASTM D4052	g/ml	0.845
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.18
Pour Point	ASTM D97	°C	-42
Magnesium, % wt	ASTM D4951	% wt	0.075
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5580
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	43
Viscosity Index	ASTM D2270	None	169
Ash, Sulphated	ASTM D874	% wt	0.8
Flash Point, PMCC	ASTM D93	°C	236

Product Performance Claims

ACEA C5
API SP
BMW Longlife-17FE+

EDGE 0W-20 LL-17 FE+
15 Sep 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com