



Product Data

Castrol EDGE 5W-30 K

Unlock maximum performance in European vehicles

Description

Castrol® EDGE® Euro Car is range of advanced full synthetic motor oils engineered to exceed manufacturer test limits, ensuring the highest level of protection and maximum performance for European cars.

European auto manufacturers create unique motor oil specifications to ensure the lubricant can withstand the intense pressure, heat and friction generated in a high output engine. Rigorous engine tests are developed, with approval granted only when the oil achieves the minimum values required in each test. Castrol® EDGE® Euro Car fluids are formulated to exceed these requirements and deliver maximum protection and performance.

Application

Castrol EDGE Euro Car 5W-30 K is designed for use in automotive gasoline and diesel engines, where the manufacturer recommends ACEA C3, ACEA A3/B4 or API SQ 5W-30.

Please refer to your owners handbook

Advantages

Castrol EDGE 5W-30 K is the natural choice for drivers who demand the highest level of protection and maximum engine performance.

Castrol EDGE 5W-30 K:

- Strong under extreme pressure, providing the highest possible wear protection
- Reduces power-robbing friction across engine speeds and conditions
- Provides excellent thermal stability and viscosity control over the full drain
- Reduces engine deposits to help maximize engine performance
- Delivers high levels of fuel efficiency and low temperature performance

Typical Characteristics

Name	Method	Units	Castrol EDGE 5W-30 K
Density @ 15C, Relative	ASTM D4052	g/ml	0.851
Viscosity, Kinematic 100C	ASTM D445	mm²/s	12
Viscosity, Kinematic 40C	ASTM D445	mm²/s	69
Viscosity Index	ASTM D2270	None	173
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5800
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	196
Ash, Sulphated	ASTM D874	% w t	0.71

Performance

ACEA C3
API SQ
BMW Longlife-04
MB-Approval 229.51/ 229.52
OPEL OV 040 1547 - G30/ D30
Porsche C30
Renault RN 0700 / RN 0710
VW 504 00/ 507 00
Recommended Specification -
ACEA A3/B4
BMW Longlife-01,
Ford WSS-M2C917-A,
MB 229.31/ 229.5,
VW 502 00 / 505 00/ 505 01

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 5W-30 K
03 Mar 2025
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com