

Castrol Alusol AD

Description

Castrol Alusol™ AD is a high performance semi-synthetic chlorine free metalworking fluid. It contains a unique additive package especially designed to machine various aluminium alloys that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Castrol Alusol AD is suitable for large central systems and single sump machines.

Application

Castrol Alusol AD is especially designed for machining of aluminium alloys. It can be used for severe machining applications including mapal reaming, deep hole drilling and tapping.

The product can also be used for machining of low-medium alloyed steel.

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding						
Milling, Turning (general machining)	✓	✓✓	✓	✓✓✓		✓
Drilling	✓	✓✓		✓✓✓		✓
Reaming, Tapping	✓	✓✓		✓✓✓		✓
Broaching				✓✓		✓

Advantages

- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Low foam in recommended water conditions
- Lubrication package specifically designed to enhance tool life and improve surface finish in aluminium machining
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components

Typical Characteristics

	Test Method	Unit	Value
Concentrate			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	40
Emulsion			
Appearance	Visual		Milky
pH (5%)	DIN 51369 ASTM E70-97		8.9
Refractometer Factor			1.0

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	✓	✓	✓	✓	-

Recommended Concentrations

General Machining	4-6%
Drilling	5-8%
Reaming and tapping	7-10%
Broaching	8-10%
Water range	5-10 ° dH

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Castrol, Alusol, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial
www.castrol.com/industrial