



GTX Diesel 15W-40 CJ-4

Passenger Car/Truck Gasoline and Diesel Engine Oil

Description

Castrol® GTX Diesel15W-40 is a premium quality diesel engine oil formulated to provide exceptional lubrication for passenger car and light truck diesel engines where API CJ-4/SN is required.

Advantages

- Provides exceptional protection from piston deposits, oil thickening and valve train wear while minimizing engine sludge formation
- Engineered to provide exceptional performance in engines operating under severe service conditions, including towing and hauling under high temperatures
- Special viscosity improvers, anti-wear, anti-oxidant and detergent additives protect and maintain cleanliness in hot running, diesel and gasoline engines.

Typical Characteristics

Name	Method	Units	Typical Result
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	15.3
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	118
Viscosity Index	ASTM D2270		136
Pour Point, max	ASTM D97	C	-36
Total Base Number, TBN	ASTM D2896	mg KOH/g	8.5
Ash, Sulphated	ASTM D874	% wt	0.99
Density @15C, Relative	ASTM D1298	g/ml	0.872
Pounds per Gallon			7.378
Flash Point, PMCC min	ASTM D93	C	200

Product Performance Claims

API CJ-4/SN

Approved - CAT ECF-3, Cummins CES 20.081, DDC Powerguard 93K218, Mack EO-O Premium Plus, RVI RLD-3, Volvo VDS 4

GTX Diesel 15W-40 CJ-4

28 Sep 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com