



Castrol Activ 4T 20W-40

Continuous Protection

Description

A motorcycle engine is at risk of damage when it's warming up, running normally and even when turned off. There are over 10 million instances per month where a motorcycle-engine could be damaged.

New Castrol Activ 4T 20W-40 has improved Actibond™ molecules that cling firmly to the engine to provide Continuous Protection through all stages of the ride, and beyond: Start up, Running and Stop.

Application

Castrol Activ 4T 20W-40 is suitable for all 4-Stroke motorcycle engines where API SL (and below) and or JASO MA-2 and MA specifications are recommended.

Advantages

Castrol Activ 4T contains Actibond™ molecules that firmly cling to engine parts and:

- Provide 75% better wear protection** during start-up
- Fight deposits and provide superior engine cleanliness during running
- Provide excellent corrosion protection, even when the engine is off

New Castrol Activ 4T delivers 50% better protection*

*vs industry limits for API SL and JASO MA2 specifications

**vs reference API SL oil in Seq IVA test

Typical Characteristics

| Name | Method | Units | Activ 4T 20W-40 |
|---------------------------|------------|--------------------|-----------------|
| Denisty | ASTM D4052 | g/ml | 0.887 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 14.0 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 122.80 |
| Viscosity Index | ASTM D2270 | None | 110 |
| Flash Point, PMCC | ASTM D93 | °C | 203 |
| | | | |

Product Performance Claims

API SL, JASO MA-2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T 20W-40

22 Aug 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customercare.india@castrol.com