



Alpha LCG 150 BX

Industrial EP Gear Oils

Description

Alpha LCG 150 BX is a zinc and chlorine free ashless extreme pressure oil formulated for industrial gear lubrication where enhanced yellow metal corrosion inhibition is a prime requirement.

Application

It is designed specifically for use in metal can body making machines where cross contamination with water miscible forming fluids can arise.

Advantages

- Advanced sulphur/phosphorus technology
- High level of anti-wear and extreme pressure protection
- Improved thermal stability
- Excellent rust protection
- Higher oxidation resistance
- Inhibited against phosphor/bronze corrosion
- Improved component life protection

Typical Characteristics

Name	Method	Units	Alpha LCG 150 BX
ISO viscosity grade	-	-	150
Density @ 20°C / 68°F	ISO 12185 / ASTM D4052	kg/m ³	890
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	150
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	14.5
Viscosity Index	ISO 2909 / ASTM D2270	-	95
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	190/374
Pour Point	ISO 3016 / ASTM D97	°C/°F	-18/0
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	20/0
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	Rating	Pass
Copper corrosion (3 hrs@100°C/ 212°F)	ISO 2160 / ASTM D130	Rating	1
Elastomer Compatibility - with SRE-NBR1	ISO 6072 / ASTM D3604	% volume change / shore hardness rating	0.5 / -2
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	>12

Subject to usual manufacturing tolerances.

Alpha LCG 150 BX

16 Dec 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>