



POWER1 ULTIMATE 4T 10W-30

Outstanding Performance

Description

With so many engine oils available in the market, don't you want to know which one offers uncompromising performance?

Castrol POWER1 ULTIMATE with Full Synthetic technology is engineered for outstanding performance across 5 critical areas.

Castrol POWER1 ULTIMATE's 5-in-1 formula delivers outstanding performance and acceleration

Application

Castrol POWER1 ULTIMATE 10W-30 is suitable for all makes of 4-stroke bikes where API SL and/or JASO MA2 are recommended.

When choosing oil, please refer to your owner's handbook and the product specifications

Advantages

Full Synthetic technology 4-stroke motorcycle engine oil.

Castrol POWER1 ULTIMATE's 5-in-1 formula delivers:

1. Excellent acceleration*
2. Excellent protection
3. Smooth riding
4. Keeps the engine cool on long rides
5. Enduring performance

Complies with requirements of catalyst equipped engines

*Acceleration benefits will be subject to riding style and oil viscosity grade

Typical Characteristics

Name	Method	Units	Castrol POWER1 Ultimate 10W-30 4T
Density @ 15C, Relative	ASTM D4052	g/ml	0.8519
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.35
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	70.58
Viscosity Index	ASTM D2270	None	154
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	207

Product Performance Claims

API SL, JASO MA2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

POWER1 ULTIMATE 4T 10W-30

08 Sep 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com