

## Castrol EDGE Professional E 0W-30

Fluid TITANIUM - Stronger Under Pressure

### Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE Professional is micro-filtered and certified CO<sub>2</sub> Neutral according to the highest global standard\*. Its patented Fluid TITANIUM transforms to be stronger under pressure and reduces friction for maximum engine performance when you need it most.

Castrol EDGE Professional with Fluid TITANIUM: unlock the true performance of your engine.

*\* in accordance with the BSI PAS 2060 specification*

### Application

Castrol EDGE Professional E 0W-30 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an ACEA C2 0W-30 lubricant.

Castrol EDGE Professional E 0W-30 is approved for use in vehicles where a Jaguar Land Rover engine oil specification STJLR.03.5007 0W-30 lubricant is required.

Please refer to your owners handbook.

### Advantages

Castrol EDGE Professional E 0W-30 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's sophisticated vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE Professional E 0W-30:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature performance

## Typical Characteristics

Name	Method	Units	Castrol EDGE Professional E 0W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.8441
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	9.8
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5252
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	52
Viscosity Index	ASTM D2270	None	176
Pour Point	ASTM D97	°C	-48
Flash Point, PMCC	ASTM D93	°C	205
Ash, Sulphated	ASTM D874	% wt	0.79

## Product Performance Claims

ACEA C2

Jaguar Land Rover engine oil specification STJLR.03.5007

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional E 0W-30

04 Dec 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: [www.castrol.co.in](http://www.castrol.co.in) Email: [customercare.india@castrol.com](mailto:customercare.india@castrol.com)