



Castrol Power 1 Scooter 2T

Get the best performance from your scooter

Description

Castrol Power 1 Scooter 2T is a high performance, low smoke 2-stroke oil designed specifically for modern scooters. Its unique Power Protection Formula has been designed to protect the exhaust system from the build up of excessive carbon deposits which can lead to a drop in engine performance over time. The condition of the exhaust in a 2-stroke engine is critical to how the engine performs. Exhaust systems can degrade rapidly in stop-start driving, especially if low quality oils are used. In the industry standard exhaust system blocking test, Castrol Power 1 Scooter 2T has been shown to out-perform current industry limits for exhaust system blocking performance. This helps to ensure that the exhaust, and therefore the engine, remains better protected against the build up of power robbing deposits over time.

Application

Castrol Power 1 Scooter 2T is suitable for use in all modern 2-stroke scooter engines. It is designed for both oil injection and pre-mix lubrication, as per manufacturers' instructions, up to a fuel:oil ratio of 50:1.

Advantages

- Power Protection Formula keeps exhaust systems clean
- Low-ash formulation helps to reduce spark plug fouling
- Excellent high temperature detergency
- Compatible with modern catalytic converters

Typical Characteristics

Name	Method	Units	Castrol Power 1 Scooter 2T
Density @ 15°C, Relative	ASTM D4052	g/ml	0.896
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.7
Pour Point	IP 15	°C	-39
Flash Point, PMCC	ASTM D93	°C	138
Ash, Sulphated	IP 163	% wt	0.05
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	79

Product Performance Claims

API TC+
ISO-L-EGD
JASO FD

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Power 1 Scooter 2T

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk