



Castrol Power 1 4T 15W-50

Power Protection Formula

Description

Castrol Power 1 4T 15W-50 is an advanced, premium quality engine oil developed for the latest generation 4-stroke motorcycle engines. Castrol Power 1 4T with Power Protection Formula is designed specifically for bikers who love the exhilaration of riding. Its Power Protection Formula is specially designed to protect the engine from the build up of power robbing deposits. It has been evaluated under harsh running conditions in a specially designed engine test and is proven to give exceptional deposit control, delivering power protection throughout the drain interval.

The added Castrol advantage of Trizone Technology™ ensures uncompromised performance protection.
Castrol Power 1 4T - engineered for performance

Application

Castrol Power 1 4T 15W-50 is designed to optimise performance and protection for modern motorcycles where API SL and JASO MA-2 are recommended.

Advantages

- Advanced 4-stroke motorcycle engine oil formulation
- Allows the engine to develop the same power as when new, even after an extended duration of speed, high load, high temperature running
- Exceptional cleanliness performance delivers power protection throughout the complete oil drain interval
- Trizone Technology™ for protection of engine, clutch and gears

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.8
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	134
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6000
Viscosity Index	ASTM D2270	None	146
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.8

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

API SL
JASO MA-2

User Advice

Health, safety and environmental information is provided for this product in the Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. Castrol will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Power 1 4T 15W-50

09 May 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com