



Product Data

EDGE 0W-30 A3/B4

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE with patented Fluid TITANIUM transforms its physical structure to be stronger under pressure to keep metal apart and reduces friction for maximum engine performance when you need it most.

Castrol EDGE with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE 0W-30 A3/B4 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends: ACEA A3/B4, API SL or earlier specification 0W-30 lubricant.

Castrol EDGE 0W-30 A3/B4 is approved for use in vehicles from leading manufacturers. Please refer to the product performance section and your owners handbook.

Advantages

Castrol EDGE 0W-30 A3/B4 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE 0W-30 A3/B4:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure
- Delivers high levels of fuel efficiency and low temperature performance

Typical Characteristics

| Name | Method | Units | EDGE 0W-30 A3/B4 |
|---------------------------|------------|--------------------|------------------|
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 63 |
| Pour Point | ASTM D97 | °C | -45 |
| Flash Point, PMCC | ASTM D93 | °C | 203 |
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.844 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 12.2 |
| Viscosity, CCS -35C (0W) | ASTM D5293 | mPa.s (cP) | 5850 |
| Viscosity Index | ASTM D2270 | None | 197 |
| Ash, Sulphated | ASTM D874 | % wt | 1.13 |

Product Performance Claims

ACEA A3/B4
API SL
BMW Longlife-01
MB-Approval 229.3/ 229.5
VW 502 00/ 505 00
Renault RN 0700 / RN 0710
Suitable for use where BMW Longlife-01 FE is specified

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

EDGE 0W-30 A3/B4
05 Mar 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2

Plant Office:3660 Lakeshore Blvd West , Toronto, ON M8W 1P2 -
Phone 1-800-268-5339 Fax 416-252-7315 Plant Office telephone: 1 800 268-5339 Trade: 1 888 CASTROL Consumer: 1 800 CASTROL Technical Inquiries: 1 800 462-0835

E-mail info@wakefieldcanada.ca Website www.wakefieldcanada.ca www.castrol.com

Page: 2/2