



Techniclean S-Premium

Multi-metal spray process cleaner

Description

Castrol Techniclean™ S Premium is an aqueous, low alkalinity industrial process cleaner containing corrosion inhibitors and biodegradable surfactants.

Application

Techniclean S Premium is designed for inter-operational and final cleaning operations of multi-metal parts and components, providing good corrosion protection on ferrous metals. It is also suited for aluminium and yellow metals.

Techniclean S Premium is suitable for use in a wide range of industrial spray and intensive flood wash machines, as well as mass vibratory finishing operations (MVF).

Techniclean S Premium effectively removes soluble oils, light duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

Conditions of Use

	Spray / Food wash	Mass vibratory finishing
Concentration Range:	1-5%	0.50%
Temperature:	up to 80°C	ambient
Spray Pressure:	up to 100 bar / 1500 psi	n/a

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Excellent demulsifying properties provide easy skimming and long bath life – reduces maintenance and disposal cost
- Low foaming at ambient temperature; allows for initial cold water start ups – economical, lowers energy cost
- Biodegradable surfactant package – improves environmental profile
- Versatile; multi-metal compatible and suitable in hard and soft water – enables possible product consolidation

Typical Characteristics

Name	Method	Units	Value
Appearance	Visual	-	Clear, pale to light yellow liquid
Density @ 15 °C	ASTM D4052	g/ml	1.09
pH (2% in DI-water)	ASTM E70/97	-	9.3
Cast Iron Corrosion Protection (3% in DI-water)	IP 287	-	Pass

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Techniclean S-Premium

26 Apr 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719

www.castrol.com/industrial