



## Castrol GTX Ultraclean 15W-40

Synthetic technology to help extend engine life

### Description

Castrol GTX is one of the world's most trusted engine oils.

The modern world creates difficult challenges for engines.

Poor fuel quality, heat and tough driving conditions can all lead to formation of sludge that potentially shortens engine life. Sludge is a sticky deposit that builds up in an engine's vital oil-ways and it can prevent oil from protecting the engine.

**Castrol GTX Ultraclean's** synthetic technology has superior performance. Its unique **Double Action formula** cleans away old sludge, and protects against new sludge formation, giving you more control over today's challenging conditions.

Help extend the life of your engine with Castrol GTX Ultraclean.

### Application

Castrol GTX Ultraclean 15W-40 is suitable for use in automotive petrol and diesel engines where the manufacturer recommends an ACEA A3/B3, API SN/CF or earlier specification 15W-40 lubricant.

### Advantages

Castrol GTX Ultraclean:

- Provides 50% superior sludge protection compared to tough industry standards\*
- Advanced protection against oxidation and thermal breakdown
- Superior protection against high temperature deposits
- Premium quality base oils and anti-wear additives that help extend the life of your engine

\*50% cleaner than the industry standard as measured in the API SN Seq. VG Sludge test

## Typical Characteristics

Name	Method	Units	Castrol GTX Ultraclean 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.875
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.5
Viscosity, CCS -20C (15W)	ASTM D5293	mPa.s (cP)	6400
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	111
Viscosity Index	ASTM D2270	None	133
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	205
Ash, Sulphated	ASTM D874	% wt	0.9

## Product Performance Claims

API SN/CF  
ACEA A3/B3

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol GTX Ultraclean 15W-40  
30 Nov 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the MSDS, available from our website for further information. No responsibility is taken by either Castrol NZ, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol New Zealand Limited  
Technical Advice Line 0800 10 40 60 Customer Service 0800 CASTROL (227 876)  
[www.castrol.co.nz](http://www.castrol.co.nz) [www.msds.castrol.co.nz](http://www.msds.castrol.co.nz)