



Castrol MAGNATEC Diesel 0W-20

CLINGING MOLECULES PROTECT FROM THE START

Description

Castrol MAGNATEC DIESEL combines dedicated diesel technology with intelligent molecules for an extra layer of protection, reducing wear during the critical warm-up period.

Its formulation protects from the moment you start, dramatically reducing engine wear*.

Now with ultra-refined molecules, for protection you can see, hear and feel.

Castrol MAGNATEC Diesel. CLinging molecules protect from the start.

** as tested in the Industry Sequence IVA wear test.*

Application

Castrol MAGNATEC Diesel 0W-20 is suitable for use in diesel engines that require a 0W-20 lubricant that Meets - Ford WSS-M2C952-A1 specification.

Advantages

Castrol MAGNATEC DIESEL is always ready to protect:

- Dedicated diesel technology maintains engine efficiency and responsiveness in common rail diesel engines
- Providing excellent soot handling performance thus minimising oil thickening

Castrol MAGNATEC's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down
- Cling to your engine forming an extra layer that protects from the moment you start;
- Bond to metal surfaces to make engine parts more resistant to wear;
- Provide continuous protection for all driving conditions, styles and temperatures.

Typical Characteristics

Name	Method	Units	Castrol MAGNATEC Diesel 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.845
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.9
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5890
Foam Sequence IV, Stability	ASTM D6082	ml	0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	38
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	207
Ash, Sulphated	ASTM D874	% wt	0.8

Product Performance Claims

Meets - Ford WSS-M2C952-A1

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol MAGNATEC Diesel 0W-20

09 Feb 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk