



Castrol EDGE Professional H 0W-20

Strength to Perform - Freedom to Drive

Description

Castrol EDGE Professional with *Fluid Strength Technology™* is Castrol's strongest and most advanced range of engine oils.

Its unique adaptive strength reduces metal-to-metal contact across a range of different driving speeds.

Castrol EDGE Professional H 0W-20 gives you the confidence to demand maximum engine performance from the latest high-performance, efficient technology engines requiring the lowest viscosity oils.

Castrol EDGE Professional H 0W-20 is co-engineered with Honda for the latest generation engines.

Micro-filtered and with its signature fluorescent colour it is your guarantee of Professional quality.

Castrol EDGE Professional. Strength to Perform - Freedom to Drive.

Application

Castrol EDGE Professional H 0W-20 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SN, ILSAC GF-5 or earlier specification 0W-20 lubricant.

Castrol EDGE Professional H 0W-20 is co-engineered with Honda for use in Honda gasoline engines that require a 0W-20 lubricant.

Advantages

Castrol EDGE Professional H 0W-20

- Maximises short and long term engine performance
- Improves engine efficiency, independently qualified
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Reduces engine deposits to help maximise engine response

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional H 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.9
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	3860
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	39
Viscosity Index	ASTM D2270	None	220
Flash Point, PMCC	ASTM D93	°C	220

Product Performance Claims

API SN
ILSAC GF5

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional H 0W-20

31 Jul 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk