



Castrol POWER1 XR 77

Ultimate 2T Racing engine oil

Description

Castrol POWER1 XR 77 is the ultimate pre-mix only racing 2-stroke engine oil based on fully synthetic technology.

Application

Castrol POWER1 XR 77 is an oil specifically developed for pre-mix use in racing 2-stroke motorcycle and kart engines.

It is not suitable for normal driving on roads, or for use in Auto-lube systems

Advantages

- High lubricity formulation to prevent seizure in high-speed conditions - allows tuners to lean out their engines to a maximum
- Provides sustained engine power throughout the race.
- Visible spark plug and piston crown deposits to enable fine race tuning - high levels of deposits and good tones give excellent readability on all unleaded fuels.
- Wet weather throttle lubrication - Castrol POWER1 XR 77 is formulated to prevent throttle slide sticking during wet conditions.
- Ease of mixing with racing gasoline - and minimal effect on the octane rating of high performance fuels allowing maximum engine compression.

Typical Characteristics

Name	Method	Units	POWER1 XR 77
Density @ 15C, Relative	ASTM D4052	g/ml	0.913
Appearance	Visual	-	Clear and bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	112
Viscosity Index	ASTM D2270	None	138
Pour Point	ASTM D97	°C	-24
Flash Point, PMCC	ASTM D93	°C	223
Ash, Sulphated	ASTM D874	% wt	0.31

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol POWER1 XR 77

20 Feb 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk