

Syntilo™ 9974

High Performance Synthetic Cutting and Grinding Fluid

Description

Castrol Syntilo™ 9974 is a mineral oil and formaldehyde releasing agent free synthetic coolant. It contains an additive package that provides good corrosion protection to machine tools and parts. The fluid also provides excellent product stability which helps to lower the overall operational costs.

Syntilo 9974 is suitable for large central systems and single sump machines.

Application

Syntilo 9974 is especially designed as a grinding, honing and heavy duty machining fluid for ferrous materials.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Titanium alloys	Tungsten Carbide
Grinding	ü	ü ü	ü ü			
Milling, Turning (general machining)	ü	ü ü	ü ü		ü ü	
Drilling	ü	ü ü	ü ü		ü	
Reaming, Tapping	ü	ü ü	ü ü		ü	
Broaching	ü	ü ü	ü ü			

Advantages

- Increased lubrication versus conventional synthetic metalworking fluids
- Excellent stability in hard and soft water applications to ensure minimal residue build up
- Rejects tramp oils to the surface of the fluid for easy skimming
- Low foaming in all water conditions
- Inhibits microbial growth to extend fluid life in central systems and individual sumps
- Prevents bi-metallic corrosion and is safe to use in equipment with copper, brass or bronze components

Typical Characteristics

	Test Method	Unit	Value
Concentrate			
Appearance	Visual		Light Yellow
Mineral oil content	Calculated	Wt%	0
Solution			
Appearance	Visual		Transparent
pH (5%)	DIN 51369 ASTM E70-97		9.3
Refractometer Factor			1.4

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding	4 – 6%
General Machining	4 – 10%
Drilling	6 – 10%
Reaming	6 – 10%
Broaching	10 – 15%

Water range 0 - 400 ppm CaCO₃

Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines
Additives	ü		ü	ü

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Syntilo™ 9974

28 Apr 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>