



Product Data

Techniclean™ MP 1

Multi-Purpose process cleaner

Description

Castrol Techniclean™ MP 1 (previously called CareClean™ MP) is an aqueous, mildly alkaline industrial multi-purpose cleaner containing biodegradable surfactants and corrosion inhibitors.

Application

Techniclean MP 1 is a multi-purpose process cleaner for precision cleaning of most metals to the most demanding specifications in a wide range of modern equipment, which includes spray and intensive flood wash as well as all types of dip and ultrasonic applications.

It is also proven to clean silicon wafers used within the solar energy industry.

Techniclean MP 1 effectively removes soluble oils, light duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

Conditions of Use

	Spray	Flood Wash	Dip	Ultrasonic
Concentration Range:	2 - 5%	2 - 5%	3 - 6%	2 - 5%
Temperature Range:	60 - 80°C	60 - 80°C	40 - 80°C	40 - 70°C
Spray Pressure:	up to 3 bar (5 psi)	up to 12 bar (200 psi)	N/A	N/A

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Leaves a temporary corrosion preventive film on the metal surface to help minimising the scrap rate which improves productivity.
- Emulsified oil separates on standing and can be skimmed off in order to increase bath-life which aids the reduction of maintenance and disposal cost.
- Biodegradable surfactant package to improve the environmental profile.
- Versatile, can be used in various applications on most metals and is suitable in hard and soft water which enables possible product consolidation.

Typical Characteristics

Description	Test Method	Unit	Value
Appearance	Visual	-	Clear, bright pale to amber liquid
Density @ 15°C	ASTM D1298	g/ml	1.09
pH of Concentrate	ASTM E70/97	-	9.3
pH, 2% in deionised w ater	ASTM E70/97	-	9.0
Cloud Point, 3% in deionised w ater	DIN EN 1890	°C	40
Cast Iron Corrosion Test, 3% dilution	IP 287	-	Pass

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called CareClean MP. The name was changed in 2015.

Techniclean™ MP 1

16 Apr 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>