



Product Data

## GTX Full Synthetic 5W-30

MAXIMUM PROTECTION TO HELP EXTEND ENGINE LIFE

### Description

The superior protection of GTX Full Synthetic helps fight the impact of heat, short trips and traffic that can all lead to sludge, potentially shortening engine life. It cleans away old sludge\* and protects against new sludge formation. It also dramatically reduces engine wear - 6X better than the industry standard.\*\*

### Application

Castrol GTX Full Synthetic 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SP, ILSAC GF-6 or earlier specification 5W-30 lubricant.

Castrol GTX Full Synthetic 5W-30 is approved for use in vehicles that require a GM dexos1® Gen 3 lubricant.

GM dexos1® approved - Gen 3: D330ACDA082, D330AACJ082, D355AVEJ082

### Advantages

Castrol GTX Full Synthetic provides:

- Superior sludge cleaning\* and protection against new formation - 1.3X better sludge protection\*\*\*
- 6X better wear protection on critical engine parts\*\*
- 3X stronger against viscosity breakdown vs. the leading full synthetic^
- Protection for 10,000 miles between oil changes^^

\*When tested in engines with high level of sludge

\*\*As measured in the latest Sequence IVA test

\*\*\*As measured in Sequence VH sludge test vs. API SP limits

^As measured in Kurt Orbahn test on 5W-30 grade

^^Up to 10,000 miles or 1 year, whichever comes first

## Typical Characteristics

Name	Method	Units	Castrol GTX Full Synthetic 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.848
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	11
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3900
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	64
Viscosity Index	ASTM D2270	None	174
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	0.92

## Product Performance Claims

API SP

ILSAC GF-6

Meets Ford WSS-M2C946-A/ WSS-M2C946-B1

GM dexos1™ Gen 3

GTX Full Synthetic 5W-30

29 Apr 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)