



PRODUCT DATA

Castrol Axle Limited Slip 75W-90 Gear Oil

Castrol Axle Limited Slip 75W-90 Gear Oil is a multi-grade gear lubricant that provides excellent performance in passenger car and light truck rear wheel and four wheel drive axles.

Features and Benefits

Castrol Axle Limited Slip 75W-90 Gear Oil meets requirements of API Service GL-5 lubricant for extreme pressure conditions and provides superior low temperature performance for smoother gear shifting and differential operation in colder climates. Maintains a thick oil film even under higher temperatures and is recommended for service fill of limited slip differentials calling for an API Service GL-5, SAE 75W-90 or SAE 75W-90 limited slip gear oil.

Warranty and Protection Requirements

Meets all passenger and light truck manufacturer's warranty requirements for vehicles, axles, or transmissions where a GL-5, SAE 75W-90 or SAE 75W-90 limited slip gear oil is specified

Industry Specifications and OEM Approvals

Meets API GL-5 requirements

Typical Properties*

| Test | Method | Typical Result |
|---|-------------|----------------|
| Viscosity at 100 °C, cSt | ASTM D-445 | 14.5 |
| Low Temperature (°C) Brookfield Viscosity cst., max | ASTM D-2983 | 119000 (-40) |
| Pour Point, °C (°F) max | ASTM D-97 | -39 (-38.2) |
| Flash Point, COC, °C (°F) min | ASTM D-92 | 143 (289) |
| Specific Gravity, 60 °F | ASTM D-1298 | 0.896 |
| Pounds per Gallon | ASTM D-287 | 7.46 |

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.



BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470
Telephone: 1,800.462.0835
Email: contactus@bp.com
©2011 BP Lubricants USA Inc. All rights reserved.

www.castrol.com/us