



## EDGE Professional C1 5W-30

Strength for Maximum Performance

### Description

Castrol EDGE Professional C1 5W-30 with Fluid Titanium Technology prevents oil film breakdown and reduces friction to help maximize engine performance. It's ready to perform however the driver and engine demand. The oil continuously responds and adapts to your engine's every need to deliver oil strength for maximum engine performance.

Inspired by the oil we produce for the engines of the world's leading car manufacturers, Castrol EDGE Professional is proud to be the world's first certified CO2 neutral engine oil and is micro-filtered. The motor oil is double filtered as part of our manufacturing process and optically check the quality of our oils with our Optical Particle Measurement System, down to the particle level. Castrol EDGE Professional products are endorsed and recommended by new car dealer partners including Audi, Jaguar, Land Rover, Mazda, Volkswagen, and Volvo. All Castrol EDGE Professional products are available to partner and non-partner OEM's.

Exclusive for New Car Dealerships.

### Application

Castrol EDGE Professional C1 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C1 specification.

Castrol EDGE Professional C1 5W-30 is a new diesel only product to meet JLR specifications for the latest generation of Land Rover V6 Diesel engines.

### Advantages

Castrol EDGE Professional C1 5W-30

- Maximizes short and long term engine performance
- Reduces engine deposits to help maximize engine response
- Sustains maximum performance even under pressure
- Independently proven to improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures

### Typical Characteristics

Name	Method	Units	Castrol EDGE Professional C1 5W-30
Density @ 15 C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	9.7
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	4012
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	52
Viscosity Index	ASTM D2270	None	177
Ash, Sulphated	ASTM D874	% wt	0.5
Pour Point	ASTM D97	degrees C	-36
Flash Point, PMCC	ASTM D93	degrees C	185

## Product Performance Claims

ACEA C1, C2

Meets Ford WSS-M2C934-B

Jaguar Land Rover - STJLR.03.5005

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60 degrees C, exposed to hot sun or freezing conditions.

EDGE Professional C1 5W-30

28 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com