



Transmax Import Multi-Vehicle

Automatic Transmission Fluid (ATF)

Description

Castrol Transmax™ Import Multi-Vehicle Automatic Transmission Fluid is for use in most Honda, Toyota, Nissan and other imported vehicles. It exceeds the requirements of the JASO-1A performance standard created by Japanese Automobile Manufacturers. This standard is recognized by Japanese OEMs in certifying ATF for use in their vehicles.

Advantages

- Enhanced friction durability for smooth transmission performance
- Exceptional high temperature protection to effectively resist fluid oxidation
- Superb low temperature fluidity for cold weather shifting

Typical Characteristics

Name	Method	Units	Transmax Import Multi-Vehicle
Specific Gravity at 60°F	ASTM D1298	-	0.859
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.4
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity Index	ASTM D2270	None	185
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	17400
Pour Point	ASTM D97	°C	-38
Flash Point, COC	ASTM D92	°C	213

Product Performance Claims

JASO 1A
Chrysler MF 7176E, MS 7176
Meets Ford Mercon, GM - Dexron IIIH

Transmax Import Multi-Vehicle
03 Feb 2023
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com