



Product Data

Castrol Motorcycle Coolant

Extended Radiator Protection

Description

Castrol Motorcycle Coolant is a pre-diluted, ethylene glycol based, fully formulated engine coolant for motorcycle and scooter applications. Castrol Motorcycle Coolant is developed with organic acid technology (OAT) making it suitable for use in a wide range of water-cooled motorcycles and scooters.

Application

Castrol Motorcycle Coolant is recommended for all categories of motorcycles and scooters. It is not recommended for use in engines with magnesium alloy parts which are in direct contact with the coolant.

Advantages

Castrol Motorcycle Coolant is designed to provide:

- anti-freeze performance down to -24°C
- protection against corrosion for longer engine life
- outstanding cooling and heat transfer properties
- protection of water system components
- compatibility with motorcycles paints in event of spillage

Typical Characteristics

Name	Method	Units	Castrol Motorcycle Coolant
Appearance	Visual	-	Clear & Bright
Colour	Visual	-	Blue/green
pH, Engine Coolants / Antirusts	ASTM D1287	-	8.5
Freezing Point, Coolant 50% vol in water	ASTM D3321	°C	-24
Density @ 20C	ASTM D1122	g/ml	1.37

Product Performance Claims

Based on coolant concentrate conforming to:
ASTM D3306(I)
BS 6580:2010

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Motorcycle Coolant

26 Jan 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk