



Castrol Activ 4T 20W-40

Essential Protection for a Trouble Free Ride

Description

Bike maintenance can be expensive, but poor engine oils can risk the essential protection of your engine, and hurt the value of your bike.

Application

Castrol Activ 4T is suitable for all 4-Stroke motorcycle engines where API SG (and below) and/or JASO MA specifications are recommended.

Advantages

New Castrol Activ 4T:

- provides essential protection for your engine
- keeps the engine clean, enables good clutch engagement and protects the gears

Typical Characteristics

Name	Method	Units	Activ 4T 20W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.8776
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.83
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	124.2
Viscosity Index	ASTM D2270	None	109
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	215

Product Performance Claims

API SG
JASO MA

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ 4T 20W-40

24 Apr 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com