



Flushing Oil

Remove dirty Oil

Description

Castrol Flushing oil is a low viscosity oil designed to flush out dirty or contaminated oil during an oil change to reduce contamination of the fresh oil.

Application

Castrol Flushing oil is suitable for use in automotive gasoline and diesel engines to flush through contaminated or very dirty oil prior to re-filling with the correct lubricant.

The engine must be warmed up and then drained before the filling with flushing oil.

Once filled run the engine at low speeds but not under load until warm and the oil has circulated but do not allow to idle for long periods.

Drain the oil thoroughly fit a new oil filter and re-fill with the correct lubricant.

Do not drive the vehicle while filled with flushing oil.

Advantages

Removes dirt and contaminants.

Removes light sludge from galleries and sump.

Reduces used oil and dirt carry over into the new lubricant fill.

Typical Characteristics

Name	Method	Units	Castrol Flushing Oil
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	5.0
Flash Point, PMCC	ASTM D93	°C	>200

Flushing Oil
11 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol K.K., East Tower 20F, Gate City Ohsaki, 1-11-2, Osaki, Shinagawa-ku, Tokyo 141-0032, Japan
Technical Advice Line: 03-5719-7777 Customer Service: 03-5719-7777
www.castrol.com