



Castrol EDGE 5W-40 A3/B4

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE with patented Fluid TITANIUM transforms its physical structure to be stronger under pressure to keep metal apart and reduces friction for maximum engine performance when you need it most.

Castrol EDGE with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE 5W-40 A3/B4 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends: ACEA A3/B3, A3/B4, API SN/CF

Castrol EDGE 5W-40 A3/B4 is approved for use in vehicles from leading manufacturers: Refer to the Product Performance section.

Please refer to your owners handbook.

Advantages

Castrol EDGE 5W-40 A3/B4 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE 5W-40 A3/B4:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure

Typical Characteristics

| Name | Method | Units | Castrol EDGE 5W-40 A3/B4 |
|---------------------------|------------|--------------------|--------------------------|
| Density @ 15C, Relative | ASTM D4052 | g/ml | 0.8522 |
| Viscosity, Kinematic 100C | ASTM D445 | mm ² /s | 12.8 |
| Viscosity, CCS -30C (5W) | ASTM D5293 | mPa.s (cP) | 6030 |
| Viscosity, Kinematic 40C | ASTM D445 | mm ² /s | 69 |
| Viscosity Index | ASTM D2270 | None | 187 |
| Pour Point | ASTM D97 | °C | -45 |
| Flash Point, PMCC | ASTM D93 | °C | 208 |
| Ash, Sulphated | ASTM D874 | % wt | 1.14 |

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
BMW Longlife-01
MB-Approval 226.5/ 229.3/ 229.5
Porsche A40
Renault RN0700 / RN0710
VW 502 00/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 5W-40 A3/B4
28 Jul 2020
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com