



Ford - Castrol Magnatec Professional A5 5W-30

Instant protection from the moment you turn the key

Description

Ford - Castrol Magnatec Professional's intelligent molecules protect from the moment you turn the key. They cling to the engine like a magnet providing an extra layer of protection, dramatically reducing* engine wear. Ford - Castrol Magnatec Professional's unique formulation delivers protection you can see, hear and feel. With micro filtration technology it's engineered for today's modern engines. Ford - Castrol Magnatec Professional. Instant protection from the moment you turn the key
* As tested in the industry Sequence IVA wear test

Application

Ford - Castrol Magnatec Professional A5 5W-30 is suitable for use in Ford gasoline and diesel engines that require an oil that meets Ford WSS-M2C-913-D, Ford WSS-M2C-913-C or earlier specifications. Ford - Castrol Magnatec Professional A5 5W-30 is also suitable for use in automotive gasoline and diesel engines where the manufacturer recommends ACEA A1/B1, A5/B5, API SN/CF or ILSAC GF-4 5W-30 lubricant

Advantages

Castrol Magnatec Professional's Intelligent Molecules:

- Cling to critical engine parts when the oil drains down
- Cling to your engine forming an extra layer that protects from the moment you turn the key;
- Bond to metal surfaces to make engine parts more resistant to wear;
- Provide continuous protection for all driving conditions, styles and temperatures.

Ford - Castrol Magnatec Professional A5 5W-30 delivers superior performance under extreme cold start up conditions relative to thicker grades

Ford- Castrol Magnatec Professional A5 5W-30 is a fully synthetic lubricant made with Ford to meet their demanding fuel economy targets, helping you drive more miles.

Typical Characteristics

Name	Method	Units	Ford-Castrol Magnatec Professional A5 5W-30
Density @ 15°C, Relative	ASTM D4052	g/ml	0.84
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.6
Viscosity, CCS -30°C	ASTM D5293	mPa.s (cP)	4680
Viscosity, Kinematic 40°C	ASTM D445	mm ² /s	54
Viscosity Index	ASTM D2270	None	164
Pour Point	ASTM D97	°C	-39
Ash, Sulphated	ASTM D874	% wt	1.24
Flash Point, PMCC	ASTM D93	°C	207

Product Performance Claims

ACEA A5/B5

API SN/CF

ILSAC GF4

Meets Ford WSS-M2C913-C/ WSS-M2C913-D

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Ford - Castrol Magnatec Professional A5 5W-30

30 Sep 2015

Castrol, Magnatec and related marks are trade marks of Castrol Ltd., used under licence.

Ford is a trade mark of Ford Motor Company, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk

Page: 2/2