



Castrol Power 1 Racing 4T 5W-40

Race Derived Technology

Description

Castrol Power 1 Racing 4T 5W-40 is fully synthetic 4-stroke engine oil for modern high performance sports bikes that increases engine acceleration and power right up to max rpm. Its Race Derived Technology based on Castrol's racing history and testing experience ensures maximum engine performance without sacrificing engine durability thus giving a significant benefit over other types of engine oils.

Castrol Power 1 Racing 4T 5W-40's formula employs the very latest Trizone Technology™ for 4-stroke motorcycles, so as to give optimum protection of the engine, clutch and gears even under the most arduous riding conditions including sustained operation at high rpm.

Application

Castrol Power 1 Racing 4T 5W-40 is designed for high performance sports bikes to deliver optimum power and protection in all conditions where JASO MA2 and MA are recommended.

Advantages

- Fully synthetic 4-stroke motorcycle engine oil featuring Trizone Technology™.
- Race derived formulation technology for max engine acceleration.
- Extreme high temperature air-cooled and water-cooled engine performance.
- Excellent high speed oil consumption control and volatility.
- Excellent shear stability to prevent viscosity break down.
- Complies with requirements of catalyst equipped engines.

Typical Characteristics

Name	Method	Units	Typical
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Appearance	Visual	-	C
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	13.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	77.2
Viscosity Index	ASTM D2270	None	171
Viscosity, CCS -30C	ASTM D5293	mPa.s (cP)	5000
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.4
Calcium, % wt	ASTM D4951	% wt	0.075

Product Performance Claims

JASO MA-2

Castrol Power 1 Racing 4T 5W-40

11 Apr 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol K.K., East Tower 20F, Gate City Ohsaki, 1-11-2, Ohsaki, Shinagawa-ku, Tokyo 141-0032, Japan

Technical Advice Line: 03-5719-7777 Customer Service: 03-5719-7777

www.castrol.com