



Transmax Axle Plus 85W-140

Multigrade axle oil

Description

Castrol Transmax Axle Plus 85W-140 is a multigrade axle oil recommended for differentials, transaxles and transmissions requiring API GL-5 oils. Suitable for both regular and turbocharged vehicles.

Advantages

- Protects gears operating under high loads.
- Prolongs component life.
- Provides excellent wear protection and durability compared to monograde oils.
- Permits operation across broad temperature range when compared to monograde oils.

Typical Characteristics

Name	Method	Units	Transmax Axle Plus 85W-140
Density @ 15C, Relative	ASTM D4052	g/ml	0.906
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	26.4
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	346
Viscosity Index	ASTM D2270	None	101
Viscosity, Brookfield @ -12C (85W)	ASTM D2983	mPa.s (cP)	42100
Pour Point	ASTM D97	°C	-24
Flash Point, COC	ASTM D92	°C	210

Product Performance Claims

API GL-5

Transmax Axle Plus 85W-140

04 Sep 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be referred to for appropriate information regarding storage, safe handling, and disposal of the product. Castrol India Limited shall not be responsible or liable for any damage or injury resulting from abnormal use of the product, from any failure to adhere to recommendations, from any failure to adhere to information regarding storage, safe handling, and disposal of the product or from hazards inherent in the nature of the product. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol India Ltd, Technopolis Knowledge Park, PO Box. 19411, 1st Floor, Mahakali Caves Road, Mumbai - 400093, India

Technical Advice Line: Customer Service - 1800 209 8100 (Tata Indicom), Phone: 022-6783 9800

Customer Service: www.castrol.co.in Email: customer-care.india@castrol.com