



Product Data

Castrol EDGE Extended Performance 0W-20

UNLOCK THE VERY EDGE OF EXTENDED PERFORMANCE

Description

There's nothing like the feel of a new car – the power, the precision, the thrill. It's a feeling drivers want to preserve for as long as possible. That's why oil endurance matters.

Modern engines are built to push limits, running hotter and harder than ever before. But intense heat leads to oxidation, deposit build-up and increased viscosity, all of which drain engine performance.

Castrol EDGE Extended Performance pushes engine oil endurance further.

Castrol EDGE Extended Performance is data-engineered for long lasting performance, delivering 60% greater oil endurance* to help protect and preserve your engine, maintaining its performance as originally designed, drive after drive.

Unlock the very edge of extended performance.

** As tested in the Sequence IIIH engine oil viscosity test versus API SP industry limits*

Application

Castrol EDGE Extended Performance 0W-20 is suitable for petrol, diesel and hybrid cars and designed to meet the latest specifications required by modern engines where the industry recommends an API SP, ILSAC GF-6 or earlier specification 0W-20 lubricant.

Typical Characteristics

Name	Method	Units	Castrol EDGE Extended Performance 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.854
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.40
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44.05
Viscosity Index	ASTM D2270	None	170
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	5454
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	202.5
Ash, Sulphated	ASTM D874	% wt	0.70

Performance

API SP
ILSAC GF-6

Castrol EDGE Extended Performance 0W-20

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. Refer to the SDS, available from our website for further information. No responsibility is taken by either Castrol Australia, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Australia Pty Limited - ABN 87 008 459 407 – 132 McCredie Road, Guildford NSW 2161, Australia
Technical Advice Line 1300 557 998 Customer Service 1300 554 890
www.castrol.com.au www.msds.castrol.com.au