



Engine Shampoo - Two Wheelers

Deep cleans to enhance engine performance and efficiency

Description

Modern riding makes two wheeler engines work harder, creating dirt and sludge that can clog vital engine parts. This can have an impact on engine operation if not fully removed during oil changes.

Castrol Engine Shampoo Two Wheelers is a pre-oil change treatment that removes up to 85% of engine sludge* thus deeply cleaning the engine.

*Based on sludge clean-up in gasoline engine testing

Application

Castrol Engine Shampoo Two Wheelers is suitable for all makes of 4-stroke automatic gearless scooters and 4-stroke motorcycles.

For best effects, use Engine Shampoo as part of every other oil change.

Conditions of Use

Usage:

1. Warm-up the engine before use to get the oil to operating temperature
2. Stop the engine and add Engine Shampoo to the existing engine oil through the filler cap.
3. Re-start and idle the engine for approximately ten minutes.
4. Stop the engine and drain the used engine oil and engine shampoo.
5. Change the oil filter and fill with new engine oil.

Precautions:

- Do not add to gasoline or diesel fuel systems.
- Do not drive with the used engine oil containing Engine Shampoo.
- Caution should be taken with hot engine oil when changing.
- Add 70 ml of Engine Shampoo for each 0.7-1.4 L of oil capacity. (Check the engine oil capacity in your owner's manual.)
- This product may freeze under extreme cold conditions.
- Do not use in Rotary or 2-stroke engines.
- For use on inside of engine only. Do not use for cleaning external surfaces or skin.

Advantages

Helps clean engine sludge to enhance your two-wheeler engine's performance and efficiency.

NB: Copy subject to local substantiation & legal approval

Typical Characteristics

Name	Method	Units	Engine Shampoo Two Wheelers
Density @ 15C, Relative	ASTM D4052	g/ml	0.8840
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.99
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	76.08
Viscosity Index	ASTM D2270	None	133
Flash Point, PMCC	ASTM D93	°C	202

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Engine Shampoo - Two Wheelers

28 Sep 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com