



Product Data

## Magnatec 0W-30 C2

CLINGING MOLECULES PROTECT FROM THE START

### Description

Castrol MAGNATEC 0W-30 C2 protects against engine wear.

Tested to meet ACEA C2 engine oil specification standards.

### Application

Castrol MAGNATEC 0W-30 C2 is suitable for use in automotive gasoline and vehicles where the manufacturer recommends an ACEA C2 specification lubricant.

### Advantages

Castrol MAGNATEC 0W-30 C2:

- Is combined with synthetic technology to provide increased protection in high and low temperature applications
- Provides continuous protection for different driving conditions, styles and temperatures

## Typical Characteristics

Name	Method	Units	Castrol Magnatec 0W-30 C2
Density @ 15C, Relative	ASTM D4052	g/ml	0.845
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	9.9
Viscosity, CCS -35C (0W)	ASTM D5293	mPa.s (cP)	6090
Viscosity, HTHS 150C	ASTM D4683	cP	2.98
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	53
Viscosity Index	ASTM D2270	None	176
Pour Point	ASTM D97	°C	-42
Flash Point, PMCC	ASTM D93	°C	206
Ash, Sulphated	ASTM D874	% wt	0.56

## Product Performance Claims

ACEA C2

PSA Approval B71 2312

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Magnatec 0W-30 C2

28 Mar 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

[www.castrol.com/uk](http://www.castrol.com/uk)