

Castrol Iloform RS 5116

Synthetic forming fluid

Description

Castrol Iloform™ RS 5116 is a fully synthetic, oil rejecting coolant containing a blend of high performance lubricity additives and a corrosion inhibitor system which provide dependable performance, when diluted with water.

Application

Iloform RS 5116 is a versatile product, suitable for use in various forming applications, such as welded tube rolling, cold rolling as well as an internal diameter lubricant for tubular hydroforming applications.

Iloform RS 5116 can also be applied for deep drawing and sawing operations of steel material.

Typical concentration range: 4 -10%.

Advantages

- Extended coolant service life
- Excellent surface finish
- Reliable protection against corrosion
- Easy to remove
- Suitable for non-ferrous metal applications
- Good demulsifying properties
- Good filterability

Typical Characteristics

	Test Method	Unit	Value
Appearance			Yellow
Relative Density @ 15°C	DIN 51 757	kg/m ³	1082
Viscosity @ 40°C	DIN 51 562	mm ² /sec	70
Mineral Oil content	DIN 51 417	% by volume	0
pH value 5%	DIN 51 361		9,1
Corrosion Protection	DIN 51 360/2		4% = Grade 0
Refractometer factor			1,35

Ester	Sulphur	Phosphorous	Chlorine	Other
				✓✓✓

Castrol, Iloform Other, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial