



## Castrol Activ CRUISE 4T 15W-50

CONTINUOUS PROTECTION

### Description

The engine in your bike risks damage all the time, when starting up, when running, and even when the engine is off.

Castrol Activ with IMPROVED ACTIBOND™ TECHNOLOGY provides 3X Protection: through start-up, while the engine is running, and when the engine is off.

### Application

Castrol Activ CRUISE 4T 15W-50 is suitable for all 4-Stroke motorcycle engines where API SN (and below) and/or JASO MA2 and MA specifications are recommended.

Not suitable for passenger cars.

### Advantages

Castrol Activ CRUISE 4T 15W-50 delivers 3X Protection\*

- Provides 50% better wear protection during start-up\*\*
- Fights deposits and provides excellent engine cleanliness during running
- Provides excellent corrosion protection, even when the engine is off

Castrol Activ CRUISE 4T 15W-50 contains IMPROVED ACTIBOND™ TECHNOLOGY that offers a protective layer to engine parts.

\*Protection in 3 stages of the ride: through engine start-up, running, and while the engine is off.

\*\*Compared to API SN limits in the Sequence IVA wear test.

## Typical Characteristics

Name	Method	Units	Castrol Activ CRUISE 4T 15W-50
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	151.8
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	213
Density @ 15C, Relative	ASTM D4052	g/ml	0.86
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	19.64
Appearance	Visual	null	Clear & Bright
Flash Point, COC	ASTM D92	°C	240
Viscosity Index	ASTM D2270	None	149

## Performance

API SN  
JASO MA2

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Activ CRUISE 4T 15W-50

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn. Bhd., Registration No. 198701007157 (165875-W), Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8, Jalan Kerinchi, 59200 Kuala Lumpur  
Phone No : 03-22818181 Toll free Line: 1-800-81-6530  
[www.castrol.com](http://www.castrol.com)