



Castrol Axle Long Drain 80W-90

Axle Fluid

Description

Castrol Axle Long Drain 80W-90 is a mineral based gear oil designed for use in axles and final drives operating under severe conditions and over a wide range of operating temperatures. It is specifically approved for use in MB Actros, MAN, Scania and ZF axles and is also recommended for other applications where API GL-5 performance is required.

Advantages

- Extended drain potential compared with conventional MB 235.0 fluids.
- Enhanced seal compatibility
- Effective wear protection under severe load conditions, ensuring longer component life and allowing it to be used in the final drives of most vehicles in a wide range of operating temperatures.
- Excellent resistance to foaming and corrosion.

Typical Characteristics

Name	Method	Units	Axle Long Drain 80W-90
Density @ 15C, Relative	ASTM D4052	g/ml	0.895
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	140
Viscosity Index	ASTM D2270	None	104
Viscosity, Brookfield @ -26C	ASTM D2983	mPa.s (cP)	130 000
Pour Point	ASTM D97	°C	-36
Flash Point, COC	ASTM D92	°C	208

Product Performance Claims

API GL-5
MAN 342 M3
MAN 341 GA1
MB-Approval 235.20
Scania STO 1:0
ZF TE-ML 05A, 12L, 12M, 16B, 17B, 19B, 21A

Additional Information

Axle Long Drain 80W-90 is registered under the following ZF approval number: ZF000229

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Axle Long Drain 80W-90
26 Jun 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com