

## Castrol ACTIV 4T

4-Stroke Engine Oil

### Description

**Castrol ACTIV 4T** is a mineral-based 15W-50 engine oil suitable for all makes of four-stroke motorcycle engines, running on either lead replacement or unleaded fuel.

**Castrol ACTIV 4T** is formulated to provide excellent engine wear protection and cleanliness. It also provides excellent wet clutch friction stability even in severe conditions. Considerable research work was done to ensure the upgraded formulation provided enhanced gear wear protection in motorcycle transmissions.

### Application

**Castrol ACTIV 4T** provides good lubrication for all street and off-road four-stroke motorcycles. It is also well suited to a wide range of four-stroke petrol engines used in generators, lawnmowers, and light power equipment.

**Castrol ACTIV 4T** is not Castrol's prime recommendation for water-cooled four-stroke marine outboards. Castrol Super Outboard 4-Stroke oil is recommended for these applications.

**Castrol ACTIV 4T** may be used for highly stressed engines, however, Castrol Power 1 Racing (4T) is the prime recommendation for competition and applications.

### Product Features and Benefits

**Castrol ACTIV 4T** offers the following key benefits:

- Provides a protective film on engine parts in all conditions.
- Significantly reduces engine wear during start-up and warm-up.
- Improved engine cleanliness, promoting longer engine life.
- Excellent wet clutch friction stability even in severe applications.
- Enhanced gear wear protection for transmission gears.

### Trizone Technology

A 4-stroke bike's performance depends on the protection of three critical zones within the bike – the **engine**, **clutch** and **gearbox**. Strong performance in all three zones is required for top performance and good component durability.

Castrol Trizone is dedicated motorcycle oil technology that has been developed specifically for improvements in motorcycle applications. All Castrol 4-stroke oils are specifically designed and tested to work and provide superior protection to these critical moving parts and this is the Castrol Trizone advantage.

## Typical Characteristics

SAE Viscosity Rating	Density @ 15 <sup>o</sup> C	KV @ 100 <sup>o</sup> C (cSt)	KV @ 40 <sup>o</sup> C (cSt)	Cold Crank Viscosity @ -20 <sup>o</sup> C	HTHS* @ 150 <sup>o</sup> C	Pour Point <sup>o</sup> C
15W-50	0.875	19.1	134	6500 cP	4.1	< - 30

*The above data is typical and does not constitute a specification.*

## Performance Levels

- Product exceeds JASO MA, MA2; API SL.

## Product Removal

Bare Metal Surfaces: Remove with Castrol solvent cleaners or water based degreasers.

Hand Cleaning: Use any of the Castrol range of hand cleaners; e.g. CareClean Plus.

Other Surfaces: Contact your local Technical Advice Line on 1300 557 998.

Castrol\_Activ\_4T\_2014\_07.docx Replaces Castrol\_Activ\_4T\_4100595\_2013\_10.docx  
July 2014

Castrol Activ 4T and the Castrol logo are trademarks of Castrol Limited, used under licence.

Castrol Australia Pty Limited, - ABN 87 008 459 407 GPO Box 5222, Melbourne VIC 3001  
Technical Advice Line 1300 557 998 / Customer Service 1300 554 890  
[www.castrol.com.au](http://www.castrol.com.au)

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, to the extent that it is permissible by law to exclude warranties and representations, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. See <http://www.msds.castrol.com.au/>. No responsibility is taken by either Castrol Australia Pty Limited, BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.